

IN THE CLAIMS

1. (currently amended) An electronic apparatus, comprising:

a main body;

a circuit in the main body functioning as a hub;

at least one first connector portion in the main body and electrically connected to the circuit; and

an electronic device having a second connector portion, the second connector portion being connected to the at least one first connector portion to directly attach the electronic device to the main body~~connected to the at least one first connector portion~~,

wherein a computer is connectable to the electronic apparatus through the circuit so that information from the computer is supplied to the electronic device and/or information from the electronic device is supplied to the computer.

2. (original) An apparatus according to claim 1, wherein power is supplied from the circuit to the electronic device.

3. (original) An apparatus according to claim 1, wherein power is supplied from the computer to the electronic device via the circuit.

4. (original) An apparatus according to claim 1, wherein the electronic apparatus is a display apparatus.

5. (canceled) ✓

6. (currently amended) An apparatus according to claim 15, wherein the at least one first connector portion is arranged on the main body so that the position of the electronic device attached thereto is desirable for the user of the electronic apparatus.

7. (currently amended) An apparatus according to claim 15, wherein the electronic apparatus is a display apparatus.

8. (original) An apparatus according to claim 7, wherein the main body includes a display screen and a supporting member for supporting the display screen, the first connector portion being integrally mounted in the supporting member.

*M* 9. (original) An apparatus according to claim 7, wherein the at least one first connector portion is arranged on the main body so that the position of the electronic device attached thereto is desirable for the user of the display apparatus.

10. (original) An apparatus according to claim 9, wherein the position desirable for the user is a position in which the electronic device faces the user.

11. (canceled) ✓

12. (original) An apparatus according to claim 1, wherein the circuit and the at least one first connector portion are formed on the basis of the USB specification.

13. (currently amended) An external apparatus, comprising:

an electronic apparatus having a main body, a circuit in the main body functioning as a hub, and at least one first connector portion in the main body and electrically connected to the circuit;

an electronic device having a second connector portion, the second connector portion being connected to the at least one first connector portion to directly attach the electronic device to ~~connected the to the~~ electronic apparatus; and

a computer connected to the electronic apparatus via the circuit for transmitting information to and receiving information from the electronic device.

14. (original) An apparatus according to claim 13, wherein the electronic apparatus is a display apparatus.

15. (canceled)✓

16. (currently amended) An apparatus according to claim 13, wherein the at least one first connector portion is arranged on the main body so that the position of the electronic device attached thereto is desirable for the user of the electronic apparatus.

17. (original) An apparatus according to claim 13, wherein the circuit and the at least one first connector portion are formed on the basis of the USB specification.

18. (currently amended) An electronic device capable of being attached to an electronic apparatus having a main body, a circuit in the main body functioning as a hub, and at least one first connector portion integrally formed in the main body and electrically connected to the circuit, the electronic device comprising:

a body;

an operating portion in the body; and

a second connector portion integrally fixed to the body the second connector portion being complementary to the at least one first connector portion so that the second connector portion directly connects to the ~~and adapted for connection to the~~ at least one first connector portion,

wherein the electronic device ~~can be~~ directly attached to the main body of the electronic apparatus and can transmit information to or receive information from a computer connected to the electronic apparatus through the circuit.

19. (original) A device according to claim 18, wherein the circuit, the at least one first connector portion

and the second connector portion are formed on the basis of the USB specification.

20. (new) An apparatus according to claim 7, further comprising:

another first connector portion in the main body and electrically connected to the circuit; and

another electronic device having a second connector portion, the electronic device and the another electronic device being of the same type, the second connector portion of the another electronic device being connected to the another first connector portion to directly attach the another electronic device to the main body,

the at least one first connector portion and the another first connector portion being positioned so that the electronic device and the another electronic device are disposed at geometrically balanced positions on the left and right sides of the electronic apparatus with respect to the user.

---